



## Metrotile Shingle



**Metrotile**<sup>®</sup>  
worldwide roofing systems

### The unique alternative to traditional shingle and slate

**Metrotile Shingle** coated steel tiles imitate the look of traditional flat asphalt shingles, but in lightweight, low-maintenance, long-life steel. They are available in different subtle duotone shades. These tiles are designed for use on roofs as well as vertical walls.

It is now possible to achieve a distinctive look without all the problems inherent in traditional asphalt shingles such as delaminating, lifting and general UV damage.

PRODUCT  
QUALITY  
**100%**  
GUARANTEED

Weatherproof  
guarantee  
of a  
*lifetime*



# Metrotile Shingle

Lightweight high grade steel with Aluzinc® coating for incredible strength and resistance. Suitable for all roof shapes.



## Specifications

Minimum pitch	15°
Maximum pitch	90°
Size of tile - overall	1335 x 300 mm
Size of tile - cover	1255 x 252 mm
Gauge of steel	.450 mm
Linear cover width	1255 mm
Coverage	0.29 m <sup>2</sup> (3.45 tiles per m <sup>2</sup> )
Weight per m <sup>2</sup>	5.9 kg
Weight per tile	1.75 kg
Colours	The available standard colours are Charcoal, Terracotta, Red, Black, Greenstone, Coffee, Walnut, Tuscany, Brindle, Antique red, Antique grey, Rustic,... Also other colours available to order (ask your dealer for more information).

## Properties



### Lightweight

Light and easy to handle and install.



### Durable

Colour stability and protects against UV light.



### Stable

Resistance to extreme wind or earthquakes.



### Strong

Exceptional strength and resistant to damage.



### Fire proof

To be conform with the European standards

## Installation of the tiles

The tiling battens for installing the Shingle tiles have to be positioned with a 250 mm spacing measured from the front batten of each batten up to the ridge.

Start at the bottom right hand side and work from right to left. Use 4 nails or screws fix each Shingle tile to the roof batten. If possible, use the cut-off from the previous to start the next course. Hook nose of upper tile into lip of tile below ensuring a tight fit. Continue with each successive course up.

At the upper course, cut the tiles to suit the ridge and attach a batten on top of the Shingle tile. Finally fix the ridge to the batten.

## More information about the installation?

Please contact your dealer.

## Accessories of the Shingle

Lorem ipsum dolor sit amet, consectetur adipiscing elit. Curabitur quis tincidunt sem. In est odio, adipiscing ullamcorper fermentum in, pellentesque vitae quam.



For a complete and detailed list of accessories and more information regarding the installation of a Metrotile roof, contact your dealer.